



Prochem PA-300

3-Part Hematology Analyzer













Prochem PA-300

3-Part Hematology Analyzer

PA-300 is a robust 3-part hematology analyzer integrating a range of advanced features intended for a cost minded and quality-focused clinical laboratory. The enhanced specification expands clinical capabilities; The brand new operating system simplifies the working process; The quality hardware components ensure reliable performance, and the improved fluidic system reduces reagent consumption. To pursuit higher satisfaction, H30 Pro empowers CBC test with maximum capabilities by

Offering up to 24 parameters including PLR and NLR

- Extending linearity range for WBC and PLT
- Differentiating WBC, RBC, and PLT with adaptive threshold
- · Requiring small sample volume for pediatric samples and difficult draw
- Simplifying the working process with an intuitive operation system
- Lowering cost with two routine reagents



Intuitive operating system




Offering NLR, PLR





Small smaple volume



Adaptive threshold

Expanded clinical capabilities

- Wider linearity range and better precision meet diversified clinical cases.
- 24-parameters test result, including NLR and PLR, helps with the prognosis of infectious and cardiovascular diseases.
- Adaptive threshold differentiates WBC, RBC, and PLT with better accuracy.
- Original hematology calibrator and controls guarantee the performance.



Simplified working process

- 10.4-inch color touch screen with an innovative operating system is simple-to-use and easy-to-navigate.
- A handheld barcode scanner allows easy entry of patient ID.
- · RFID transducer secures the distributors' reagent business.
- A built-in thermal printer allows for a fast printout of test reports.
- The memory contains up to 100,000 results, including histograms.
- Up to 60 QC files with 100 QC data for each can be stored.
- Support external printer, barcode scanner, mouse, and keyboard for flexible connection options.
- · Bidirectional LIS connectivity via HL7.

Effective cost control

- Two routine reagents for sample analysis, up to 120 days on-board stability plus low reagent consumption, provide cost-effective results.
- · Reliable diagnostics keep costs to a minimum.
- · Minimal maintenance ensures maximal uptime.

Technical Specifications

Performance	Specification & Features		
Parameters	24 reportable parameters: WBC, LYM%, MID%, GRA%, LYM#, MID#, GRA#, RBC, HGB, HCT, MCV, MCH, MCHC, RDW-CV, RDW-SD, PLT, MPV, PDW-CV, PDW-SD, PCT, PLCC, PLCR 2 RUO parameters: *NLR, *PLR 3 histograms for WBC, RBC and PLT		
Principles	Direct impedance method for WBC, RBC and PLT counting. Cyanide free Lyse reagent for hemoglobin test.		
Sample Volume	Whole blood 10 μL, Capillary Whole Blood 10 μL, Pre-diluted 20 μL		
Reagent	HD310 Diluent 10L/20L HL310 Lyse 200mL/500mL/1L HC310 Cleaner 50mL		
Performance	Parameter WBC(10°/L) RBC(1012/L) HGB(g/L) PLT(109/L) MCV(fL)	Linearity Range 0.0-300 0.0-8.5 0-250 0-4000 70-120	Precision (CV %) ≤3.0% (3.50-7.00) ≤2.5% (7.01-15.00) ≤1.5% ≤1.5% ≤5.0% ≤1.0%
Control and Calibrator	PA-30D, PA-CAL PLUS		
Throughput	60 samples per hour		
Data Storage Capacity	100, 000 results including results and histograms, 60 QC files (100 data per file)		
Operating Environment	Temperature : 15°C~35°C; Humidity : 20% RH~85% RH; Air pressure : 70 kPa~106 kPa		
Dimension and Weight	415mm(L) x 275mm(W) x 406mm(H); 18kg		

HEAD OFFICE

™ info@promea.in

\(+91 91549 38441

Manufactured by:

Promea Theraputics Pvt. Ltd.

M4, Medical Device Park, Sultanpur, Patancheru (M), Sangareddy (Dist), Hyderabad, Telangana, India - 502319.







